

TRUCK & BUS TIRES



LWT26

- Low rolling resistance and anti-wear formula design.
- Excellent water evacuation performance.
- Irregular wear resistance.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	M	9.00	14.5
315/80R22.5	20	157/154	M	9.00	14.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	10.5
11R22.5	18	148/145	L	8.25	10.5

LWT32

- Bionic pattern provides excellent driving and braking performance.
- Four advanced longitudinal grooves and pressure control technology ensure comfortable driving experience.
- Abrasion-resistant compound provides long mileage and prevents from eccentric wear.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
7.50R16	16	125/121	L	6.00	13.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	M	9.00	15.0

LWT35

- Excellent anti-sideslip performance, low rolling resistance and noise.
- Enclosed shoulders prevent the tyres from eccentric wear.
- Four longitudinal grooves and smooth shoulders deliver outstanding high-speed performance.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	20	156/150	M	9.00	15.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.5R17.5	18	143/141	L	6.75	13.5
11R22.5	18	148/145	M	8.25	13.5
11R24.5	18	149/146	M	8.25	13.5
215/75R17.5	18	135/133	L	6.00	12.0
235/75R17.5	18	143/141	L	6.75	13.0
295/80R22.5	18	152/149	M	9.00	16.0

LW3

- Excellent pattern design, with excellent traction and braking.
- Tire tread pattern groove heat dissipation efficiency, excellent drainage performance.
- Special formula structure design, small rolling resistance, wear resistance, oil saving.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
13R22.5	20	156/153	J	9.75	18.0
325/95R24	22	162/160	K	9.00	15.5
12.00R20	20	156/153	J	8.50	17.0
295/80R22.5	18	152/149	L	9.00	16.0
315/80R22.5	20	157/154	L	9.00	16.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
385/65R22.5	20	160	K	11.75	14.5

LT01

- The longitudinal four-pattern design effectively improves the maneuverability and anti-sideslip.
- Zigzag pattern groove design, effectively prevent gravel.
- The unique wear-resistant tread formula makes it have excellent wear resistance.
- The special groove design of shoulder effectively reduces the stress concentration of shoulder and reduces the abnormal wear of shoulder.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	10.5
11R22.5	18	148/145	L	8.25	10.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	10.5
11R22.5	18	148/145	L	8.25	10.5

LWT31

- Four zigzag grooves and robust longitudinal ribs are designed to reduce braking distance and to enhance driving safety.
- Ejectors at the bottom of grooves prevent stones trapping.
- Innovative compound of shoulders reduce pattern contact pressure and irregular wear to increase mileage.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	M	9.00	15.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	M	9.00	15.0

LWT33

- Increased sidewall duration and low rolling resistance.
- Extreme ease in measuring sidewall wear.
- Improved grip on wet and slippery surfaces.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.5R17.5	18	143/141	L	6.75	13.5
11R22.5	18	148/145	M	8.25	13.5
11R24.5	18	149/146	M	8.25	13.5
215/75R17.5	18	135/133	L	6.00	12.0
235/75R17.5	18	143/141	L	6.75	13.0
295/80R22.5	18	152/149	M	9.00	16.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	26.0
12.00R20	20	156/153	E	8.50	26.0

LWT39

- The structure of 5 zigzag grooves provides excellent traction and directional driving performance, as well as cornering stability.
- Special tread bottom design provides excellent drainage performance.
- Optimized tread formula and optimized design provide the tyres with excellent mileage and balancing.
- Ladder-like shoulders effectively reduce heat and prevent uneven wear.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
385/65R22.5	20	160	K	11.75	14.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	18	149/146	L	8.25	15.5
295/80R22.5	18	152/149	L	9.00	16.0
315/80R22.5	20	157/154	L	9.00	16.0

LWM86

- Unique block pattern provides excellent traction and braking performance.
- Cut resistant and low heating-up formula deliver outstanding mileage.
- Robust carcass provides maximum load-bearing capacity.
- Optimized tread effectively improves its self-cleaning ability.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	K	7.50	20.0
11.00R20	18	152/149	K	8.00	19.0
12.00R20	20	156/153	K	8.50	18.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	K	7.50	20.0
11.00R20	18	152/149	K	8.00	19.0
12.00R20	20	156/153	K	8.50	18.5

LWM88

- The classic big "S" mineral pattern provides a strong and powerful grip.
- The groove ditch with full radian patterns can effectively prevent groove cracks, and has excellent drainage and mud discharge performance.
- Strong belt layer design, strong impact resistance, suitable for harsh road conditions.
- Mine-specific formula, anti-puncture, no cracking, no falling blocks.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	23.5
12.00R20	20	156/153	E	8.50	22.5
12.00R20	20	156/153	E	8.50	25.5
12R22.5	18	152/149	E	9.00	23.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	23.5
12.00R20	20	156/153	E	8.50	22.5
12.00R20	20	156/153	E	8.50	25.5
12R22.5	18	152/149	E	9.00	23.5

LWM99

- The horizontal groove design ensures the driving performance of the tire.
- Deepened pattern and high-saturation design of pattern blocks improve the tire's puncture resistance and effectively prevent run-flats.
- The stone ejector design at the bottom of the ditch effectively prevents punctures and ditch cracks.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	26.0
12.00R20	20	156/153	E	8.50	26.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	E	7.50	21.5
11.00R20	18	152/149	E	8.00	21.5
12.00R20	20	156/153	E	8.50	21.5

LWS23

- Widened tread design with better running stability.
- New low heat tread formula provides excellent high-speed performance.
- Special tread bottom design provides excellent drainage performance, as well as cornering stability.
- Optimized tread formula and optimized design provide the tyres with excellent mileage and balancing.
- Ladder-like shoulders effectively reduce heat and prevent uneven wear.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	18	149/146	L	8.25	15.5
295/80R22.5	18	152/149	L	9.00	16.0
315/80R22.5	20	157/154	L	9.00	16.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	17.0

LWM82

- Reinforced structural design greatly improves the safety performance of tires.
- Unique pattern on the crown delivers good appearance.
- Stepped grooves on the tread deliver good anti-puncture performance and stone-ejection.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	E	8.50	26.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	E	8.50	26.0

LWM87

- Large lateral tread provides strong traction and prominent performance for the off-road.
- Reinforced tire bead and special designed mining pattern are suitable for bad road conditions and overloading.
- Good property of self-cleaning and high gripping performance suits for muddy road.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.00R20	16	144/142	K	7.00	20.0
10.00R20	18	149/146	K	7.50	21.0
11.00R20	18	152/149	K	8.00	23.0
12.00R20	20	156/153	K	8.50	23.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.00R20	16	144/142	K	7.00	20.0
10.00R20	18	149/146	K	7.50	21.0
11.00R20	18	152/149	K	8.00	23.0
12.00R20	20	156/153	K	8.50	23.0

LWM89

- Reinforced carcass, bead and 0 angle structure on the shoulders provide high quality and good performance under heavy load conditions.
- Lateral grooves with wide angles increase driving power and self-cleaning ability.
- Thickened sidewall enhances out and impact resistance. Strengthened groove bottom enhances puncture resistance on unpaved road.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	24.5
12.00R20	20	156/153	E	8.50	26.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	E	7.50	21.5
11.00R20	18	152/149	E	8.00	21.5
12.00R20	20	156/153	E	8.50	21.5

NDRS01

- Longitudinal four grooves pattern design with the stone ejector at the bottom strengthens the resist of puncture and prevent cracks, also has good heat dissipation and drainage performance.
- Good controllability, effectively prevent the flicking and edge blocks from grinding and breaking, and provide good carrying performance.
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	17.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	17.0

LWD68S

- Widened tread design.
- Good heat dissipation performance.
- Excellent braking driving performance.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	K	9.00	21.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	K	9.00	21.5

LWD79

- Super wide driving surface with stronger driving stability.
- Large tread block design with excellent driving and braking performance, safer handling.
- Reinforced case and bead design with excellent durability and loading performance.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	K	9.00	21.0
315/80R22.5	20	157/154	K	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	K	9.00	21.0
315/80R22.5	20	157/154	K	9.00	22.0

LWM68

- Reinforced structural design greatly improves the safety performance of tires.
- Unique pattern on the crown delivers good appearance.
- Stepped grooves on the tread deliver good anti-puncture performance and stone-ejection.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	24.5
12.00R20	20	156/153	E	8.50	26.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	24.5
12.00R20	20	156/153	E	8.50	26.0

LWM81

- Mixed large tread, wide tread cap and deep tread pattern provide excellent traction.
- Optimized and reinforced tire bead, special designed mine pattern are made for rough road and overloading ability.
- Anti-cutting compound prevents cutting and stabbing, which especially suits for rough road.

POSITION

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	K	8.00	19.0
12.00R20	20	156/153	K	8.50	



LW801

- Applicable to national highway, high speed and high grade pavement.
- Especially suitable for medium and long distance transportation, with good guiding performance.
- Features: anti-sideslip, good drainage, heat dissipation performance, stone ejector pattern design, long mileage.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	15.5
11R22.5	18	148/145	M	8.25	15.5
235/75R17.5	18	143/141	J	6.75	13.0
285/70R19.5	18	150/148	J	8.25	13.0
265/70R19.5	16	140/138	L	7.50	14.0
265/70R19.5	18	143/141	J	7.50	14.0
295/75R22.5	16	146/143	L	9.00	14.5

△ LW801H

LW806

- The three middle grooves provide good guiding and drainage properties, which are suitable for guiding and drag wheel position.
- Using the low heat rubber in the tyre tread base ensures excellent durability and wear & cut resistance.
- The upper tread rubber formula ensures the excellent cut, tear and abrasion resistance.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	18	148/145	M	8.25	17.5
315/80R22.5	20	156/150	M	9.00	18.0
11R22.5	16	146/143	M	8.25	17.5

△ LW806H

LW663

- Horizontal block pattern provide excellent traction and braking ability.
- Opened shoulders with good self-cleaning ability reduce heat generation.
- Unique compound enhances tyres' speed performance and driving distance.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	19.0

LW901

- Suitable for long-distance mixed road transportation.
- The rubber in the middle of the crown is highly saturated, durable and wear-resistant, and the longitudinal groove design has good heat dissipation performance.
- Excellent block pattern design to achieve maximum power transmission.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
235/75R17.5	18	143/141	J	6.75	15.0
315/70R22.5	18	152/148	M	9.00	20.0
315/80R22.5	20	156/150	M	9.00	20.0



LW902

- Provide a longer mileage.
- Provide excellent driving and grips performance.
- Enhance the grip performance on wet roads.
- Reduce tread heat generation, and deliver excellent durability.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	18	148/145	M	8.25	19.0
11R24.5	18	149/146	M	8.25	19.0
11R22.5	18	149/146	K	8.25	23.0
11R24.5	16	149/146	K	8.25	23.0
295/75R22.5	16	146/143	K	9.00	23.0

△ LW902H

LW805

- Four longitudinal grooves are adopted for excellent handling stability and ride comfort at high speed.
- Horizontal grooves and special tiny spines on the tread improve drainage performance and silt resistance.
- New tread formula is created for outstanding abrasion resistance.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	16.0
315/70R22.5	18	152/148	M	9.00	15.0
315/80R22.5	20	156/150	M	9.00	16.0

LW807

- Provide excellent anti-skid and handling performance.
- Effectively increase tyre's driving performance, reduce heat generation and improve durability.
- Reduce tread heat generation, and deliver excellent durability.
- Provide excellent wear resistance performance.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
385/55R22.5	20	160/158	K/L	12.25	15.0
385/65R22.5	24	164	K	11.75	14.5

LW900

- The geometric design of grooves ensures easily self-cleaning, better traction and even wear.
- Added protection at the bottom of grooves effectively avoids stone trapping and gives better resistance.
- Aggressive directional tread with robust blocks provides extra traction for various road conditions.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	20.0
13R22.5	18	156/150	L	9.75	18.0
315/80R22.5	20	156/150	L	9.00	20.0



NDH33RA

- The pattern design has stone ejector, good heat dissipation performance and drainage performance.
- It is suitable for high-speed and high-grade paved roads and trailers.
- The steering/trailer wheel of the matching vehicle has good control performance, effectively prevents side slip, and provides good carrying performance.
- It has excellent wear resistance, low heat generation, low rolling resistance, environmental protection and fuel saving.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0
235/75R17.5	18	143/141	J	6.75	17.0
315/80R22.5	22	158/156	J	9.00	22.0
325/95R24	22	162/160	K	9.00	23.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	24.0
295/80R22.5	18	152/149	J	9.00	22.0

△ LW808+ △ LW808H



LW917

- It has a wide tread and a deep design of pattern, which has strong traction and grip.
- The block design gives the tyre excellent wear resistance and tear resistance.
- The pattern block is step-like and the design of rubber nails are added to the bottom of the groove, which has excellent stone-removing and silt-removing performance.

POSITION 

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	22	158/155	F	8.50	25.0
235/75R17.5	18	143/141	J	6.75	17.0
315/80R22.5	22	158/156	J	9.00	22.0
325/95R24	22	162/160	K	9.00	23.5

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0